

LUXPRO®**PSP711RF**

PSP711RF DIGITAL PROGRAMMABLE THERMOSTAT

- **Remote Controlled Temperature Control From Anywhere in House**
- **Easy Programming with LUX Speed Dial®**
- **7 Day Programming - 4 Periods Per Day**
- **Smart Recovery**
- **Default ENERGY STAR® Approved Program**
- **Lighted Display**
- **Vacation Hold**
- **Keyboard Lockout**
- **2 or 5 Minute Delay**
- **Temporary Temperature Override**
- **Fahrenheit or Celsius Temperature Display**
- **12/24 Hour Clock**

COMPATIBLE WITH:

- Low Voltage (24 Volt) Systems
- Single Stage Heat Pumps
- High Efficiency Systems
- Millivolt Systems (Wall Furnace)
- 1 Heat/1 Cool Heating and Air Conditioning Systems, Gas, Oil or Electric Heating Systems

NOT COMPATIBLE WITH:


- 2 Stage Heat Pump Systems
- 3 Wire Hot Water Systems
- 120/240 Line Voltage System

LUX PRODUCTS CORPORATION

6000 I Commerce Parkway • Mt. Laurel, NJ 08054 • (856) 234-7905 • FAX (856) 234-7825 • www.luxproproducts.com

LUXPRO[®]

PSP711RF



**Six (6) AA Batteries Required
(2 Remote, 4 Thermostat) Included**
WARNING: Use Energizer[®] or DURACELL[®] Alkaline Batteries Only.
Energizer[®] is a registered trademark of Eveready Battery Company, Inc.
 DURACELL[®] is a registered trademark of The Gillette Company, Inc.

GENERAL DESCRIPTION:

6¼" (160mm) wide x 3⅞" (100mm) tall x 1¼" (30mm) deep

Description: Digital Thermostat offers programmable control of single stage heating and cooling systems. Temperature control adjustable.

SPECIFICATIONS:

Heat/Cool Terminals: Y, O, G, W, B, RH, RC.

Electrical Ratings: 1½ AMPS at each terminal, 2 AMPS total 24v AC.

Battery Powered: 4 "AA" Batteries (Thermostat) - 2 "AA" Batteries (Remote).

Temperature Control Range: 45°F to 90°F (7° to 32°). Accuracy: ±1°F over a range of 50°F to 95°F.

Environmental Limits:

Moisture and Dust: meets IP20.

Operating Humidity: 20% to 90% non-condensing.

Operating Temperature: +32°F to +95°F (+0°C to +35°C).

Storage Temperature: -4°F to +130°F (-20°C to +54°C).

Electrical Immunity: meets relevant CE specifications.

WARNING: Use Energizer[®] or DURACELL[®] Alkaline Batteries Only.

Energizer[®] is a registered trademark of Eveready Battery Company, Inc. - DURACELL[®] is a registered trademark of The Gillette Company, Inc.



LUX Products Corporation 6000 I Commerce Parkway • Mt. Laurel, NJ 08054
 (856) 234-7905 • FAX (856) 234-7825 • www.luxproproducts.com

JOB NAME: _____ DATE: _____

CONTRACTOR: _____ UNIT DESIGNATION: _____

ENGINEER: _____ MODEL NO.: _____

SUBMITTED FOR: APPROVAL RECORD LOCATION: _____